

## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

Claims 1-14 (canceled)

15. **(New)** In a fuel injection system for internal combustion engines, having a high-pressure reservoir (15), which is subjected to fuel at high pressure via a high-pressure feed unit (8) and supplies fuel injectors (19) with fuel, and the high-pressure feed unit (8) is assigned a pressure regulating valve (12) which is disposed between a high-pressure side (10, 56) and a low-pressure side (11, 53) and includes a valve element (54), which is triggerable via an electrical final control element (47), the improvement wherein the pressure regulating valve (12) comprises a housing component (41), which includes a deformable region (57) by way of which upon mounting of the pressure regulating valve (12) on a receiving body (52) that carries high pressure, a gap L between faces (48, 49) of an electrically triggerable final control element assembly (45, 47) is adjustable.

16. **(New)** The fuel injection system of claim 15, wherein the housing component (41) of the pressure regulating valve (12) that includes the deformable region (57) is embodied as a housing body.

17. **(New)** The fuel injection system of claim 16, wherein the deformable region (57) on the housing component (41) is located in a region which in the mounted state of the pressure regulating valve (12) on a receiving body (52) is surrounded by the receiving body.

18. **(New)** The fuel injection system of claim 16, wherein the housing component (41) comprises a mounting element (51) that is movable relative to the outside of the housing component.

19. **(New)** The fuel injection system of claim 15, wherein the deformable region (57) on the housing component (41) of the pressure regulating valve (12) is formed by a wall thickness reduction (59, 59.1).

20. **(New)** The fuel injection system of claim 15, wherein the deformable region (57) on the housing component (41) of the pressure regulating valve (12) is formed by recesses (60) oriented perpendicular to the action line (58) of the mounting force.

21. **(New)** The fuel injection system of claim 20, wherein the recesses (60) are embodied as through bores.

22. **(New)** The fuel injection system of claim 20, wherein the recesses (60) are embodied as blind bores.

23. **(New)** The fuel injection system of claim 18, wherein the mounting element (51) is secured in the axial direction on the outside of the housing component (41) of the pressure regulating valve (12) by a support ring (65).

24. **(New)** The fuel injection system of claim 15, further comprising an armature plate (46) acted upon by a spring element (44), the armature plate (46) being disposed on the connection end of the housing component (41) of the pressure regulating valve (12), and an air gap L formed between the face end (48) of the armature plate and a face end (49) of the housing component (41) that surrounds an electromagnet (47).

25. **(New)** The fuel injection system of claim 15, further comprising a seat ring (64) that has a valve seat (55) for the valve element (54), the housing component (41) of the pressure regulating valve (12), on the end toward the valve, surrounding the ring seat.

26. **(New)** The fuel injection system of claim 25, wherein the seat ring (64) comprises a throttle restriction, which serves on the high side as an outlet throttle with respect to the system pressure inside a hollow chamber (46) of the receiving body (52) and which can be opened and closed by the valve element (54).

27. **(New)** The fuel injection system of claim 25, wherein the deformable region (57) of the housing component (41) extends in the axial direction (61) between a sealing element (62) and the seat ring (64).

28. **(New)** The fuel injection system of claim 1, wherein the deformable region (57) of the housing component (41) of the pressure regulating valve (12) is elastic and/or plastic, depending on the mounting force (58) brought to bear at the mounting element (51).